

DAD'S EASY SPRAY TECH DATA SHEET

Paint & Varnish Remover

Product# 638

Available Sizes: Qt., Gal., 5Gal.

SPRAYABLE STRIPPER

GENERAL DESCRIPTION

Dad's Easy Spray stripping gel is designed to remove multiple layers of finish in one application. This Methylene Chloride Free, semi-paste formula clings to rounded and vertical surfaces to make paint removal easy. It quickly attacks the finish and lightens wood stain but will not harm wood or corrode metal.

RECOMMENDED USES

Use on wood, metal and masonry. Effectively removes most latex and oil-based paint, lacquer, shellac, varnish, epoxy and polyurethane finishes.

DIRECTIONS FOR USE

Use this product outdoors if possible. If used indoors, provide plenty of fresh air by opening all doors and windows to achieve cross ventilation. Do not use in basement or other unventilated areas. Follow use, prime and care instructions on sprayer bag. Remove plastic filter on end of tube. White cap on tube is not required for use.

Application: Open container carefully. Protect hands with solvent resistant gloves. Wear glasses or goggles to protect eyes. Apply to area no larger than two feet by two feet at a time. Do not brush back and forth like paint. Allow the remover to stand undisturbed until the old finish softens enough to be removed with a putty knife.

Clean Up: Use steel wool or a stiff brush for hard to get at places. Some finishes may require more than one application. To remove any remaining deep stain from wood, scrub with household bleach or oxalic acid solution and steel wool. Cool water and a scrub brush may be used for a final rinse. On fine wood and veneers use mineral spirits to prevent warping or raising the grain. Allow to dry thoroughly before refinishing. Rags and other waste should be allowed to completely air dry, and then disposed of in trash collection. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Temperature Guidelines: Use at temperatures between 65° F and 85° F only.

PERCAUTIONS

Caution: EXTREMELY FLAMMABLE! KEEP AWAY FROM ALL SOURCES OF IGNITION! This product can cause damage to most materials on contact. Avoid contact with all surfaces except those being worked on. Damages rubber, asphalt tile, plastic, fiberglass, and other synthetic materials. Product should be stored in a cool place, kept tightly capped and used within six months.

EXTREMELY FLAMMABLE! KEEP AWAY FROM ALL SOURCES OF IGNITION! Keep away from heat, sparks and flame. Vapors are given off rapidly during use and may ignite explosively. Vapors are heavier than air and may travel long distances to other rooms or lower areas. DO NOT use in confined areas such as basements or bathrooms. IF WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT. USE THIS PRODUCT OUTDOORS IN AN OPEN AREA. It is dangerous to use indoors. If used indoors open all doors and windows to provide plenty of fresh air cross ventilation equal to outdoor conditions to avoid vapor buildup. DO NOT smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may linger for 30 minutes or more after use. If you smell solvents, vapors are still present. Do not turn ignition sources on or relight pilot lights until certain that all vapors are gone. Due to fire hazard, do not apply to floors or other large areas. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency. Close container after each use. Do not transfer to unlabeled containers. Do not use for stripping floors or any place where a flammable remover might be hazardous. Use over a small area because health and safety risks will increase dramatically when used over large areas. Harmful to plastic or other synthetic materials.

Health Hazards: Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area to obtain fresh air. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. May be harmful if absorbed through the skin.

FIRST AID

First Aid: If swallowed, DO NOT induce vomiting. GET IMMEDIATE MEDICAL ATTENTION! Call physician or hospital emergency room or poison control center immediately. In case of eye contact, flush thoroughly with water for at least 15 minutes. Get medical attention. For skin contact, wash thoroughly for at least 15 minutes. Get medical attention if irritation persists. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention.

KEEP OUT OF REACH OF CHILDREN.

PRODUCT DATA

CALIFORNIA PROP 65: WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Contains: METHYL ALCOHOL, 1,3-DIOXOLANE, DIMETHYL CARBONATE, ACETONE, AND PETROLEUM DISTILLATES. Cannot be made non-poisonous.

Refer to SDS for additional product information.



sunnyside

Sunnyside Corporation

225 Carpenter Ave.

Wheeling, IL 60090

800-323-8611

www.sunnysidecorp.com